



BL021000 Marine FC-W Engine Oil 4-Stroke Outboard EHP 10W-40

Verzija dokumenta: 22.04.2024.



opis

Ovo Marine FC-W Engine Oil 4-Stroke Outboard EHP pruža odličnu zaštitu i u teškim uslovima i osmišljeno je za upotrebu u 4-taktnim brodskim i vanbrodskim motorima sa vodenim hlađenjem. Ovo motorno ulje zadovoljava najnovije zahteve NMMA. Posebno je pogodno za motore Mercruiser, Mercury, Suzuki, Honda, Yamaha, Nissan, Johnson/Evinrude, Chrysler Marine itd.

Prema specifikacijama

API SL
NMMA FC-W (Certificate number: FB-44404M)

Jedinice pakovanja

| ART. BR. | KOLIČINA | KOMADA PO JEDINICI | KOMADA PO PALETI |
|-----------|----------|--------------------|------------------|
| BL021001 | 1 L | 6 | 450 |
| BL021005 | 5 L | 4 | 112 |
| BL021020 | 20 L | 1 | 30 |
| BL021060 | 60 L | 1 | 6 |
| BL021205 | 205 L | 1 | 2 |
| BL021999 | 1000 L | 1 | - |
| PBL021000 | 1 L | 1 | - |

Standardne analize

| TEST | VREDNOST | METHOD |
|------------------------------|----------|--------------------|
| Density na 15°C | 0.88 | kg/l |
| Viscosity SAE | 10W-40 | |
| Kinematic Viscosity na 100°C | 14.3 | mm ² /s |
| Viscosity Index | 156 | |
| Dynamic Viscosity na -25°C | 6300 | mPa.s |
| Flashpoint COC | 216 | °C |
| Pourpoint | -30 | °C |
| Total Base Number | 7.7 | mgKOH/g |

Ove karakteristike su tipične za tekuću proizvodnju. Može doći do varijacija u ovim karakteristikama.