



18000VW Gearbox Oil 75W GL-4 Premium Synthetic

Document version: May 13, 2024



Description

This premium synthetic SAE 75W VW FE transmission oil has been developed for use in VW manual transmissions, among others, and for those applications for which manufacturers require a SAE 75W GL-4 specification.

Application manual

According to the specifications of

API GL-4+
BMW MTF LT-2 / MTF LT-3 / MTF LT-5
Fiat 9.55550-MZ2
Ford WSD-M2C200-D2 / WSD-M2C200-D3 / WSD-M2C200-E1
Jaguar/Land Rover STJLR GX73-M1R564-AA
Nissan 32001 1BY0A / LV MTF-1
Opel/GM 1940004
PSA 9730 A8
Toyota 08885-81001 / 08885-81081
VW G 055 512
VW G 052 171 / 052 178 / 052 512 / 052 527 / 052 549 / 052 726 / 052 798 / 055 726 / 060 726 / 070 726
Volvo 1161838 / 1161839

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
18001VW	1 L	6	450
18004VW	4 L	4	112
18020VW	20 L	1	30
18060VW	60 L	1	12
18205VW	205 L	1	2
18999VW	1000 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.856	kg/l	
Viscosity	75W		
Kinematic Viscosity at 40°C	29.93	mm ² /s	
Kinematic Viscosity at 100°C	6.31	mm ² /s	
Viscosity Index	169		ASTM D2270
Flashpoint COC	210	°C	
Pourpoint	-42	°C	
Brookfield Viscosity at -40°C	13800	mPa.s	ASTM D2983

These characteristics are typical of current production. Variations in these characteristics may occur.